

# LED Battens

## Uni Batten IP20



### Features

- Traditional batten profile.
- Surface mountable or suspendable.
- No external junction box required.
- Broad 120° beam angle.
- Available with built-in sensor and tri-colour models.
- IK08 rating.

The Emerald Uni Batten IP20 is built around a philosophy of delivering ease of installation with high efficiency.

The Uni IP20 Batten Series maintains a traditional batten profile and offers versatile installation options, allowing for both surface and suspension mounting. With a broad 120° beam angle, it provides wide illumination, while its IK08 rating ensures durability in various environments. The series is available in models with a built-in sensor and tri-colour options, featuring dual motion and lux sensors for enhanced control—all without the need for an external junction box.

### Specifications

Power factor	>0.9
CRI	>80
Beam angle	120°
IP rating	20
Lifetime (L70)	>60,000hrs
Warranty	5 years

Model	CCT	Dimensions (mm)	UGR	LCP	Sensor	Watt	Lumens	Efficacy
EP-UNI-620-10	5000K	L1221xW71.3xH76	>22	9.78	No	10	1394.2	143lm/W
EP-UNIG3-1220-15	5000K	L1221xW71.3xH76	>22	14.93	No	15	2523.8	169lm/W
EP-UNIG3-1220-25	5000K	L1221xW71.3xH76	>22	24.22	No	25	3153.1	130lm/W

